

SCAFFOLD SQUARE STORAGE RACK



PART NUMBER	DESCRIPTION	WEIGHT (LBS.)	DIMENSIONS (INCHES) LENGTH X WIDTH X HEIGHT	MAX. CAPACITY (LBS.)
SSR	Square Steel Rack	134	44.25 x 44.25 x 32.25	5,000

Third-party manufactured component. Data may vary.

Square steel racks are designed to hold InstantLock 2 verticals, diagonals and other irregularly-shaped components.

When shipping, the square racks require two (2) pieces of banding to be placed around the base of the rack and the items being carried.

Square steel racks are designed so special casters can be placed on the bottom to allow the racks to be easily moved without a forklift. Always inspect rack feet for damage before installing casters or loading the rack.



STORAGE:

1. Square steel racks may be stacked for storage. The strength of the storage surface will determine how many racks can be stacked.
2. On grass, dirt or other unpacked surfaces, racks should be placed singly.
3. On prepared surfaces and asphalt, racks can be placed two (2) or three (3) high.
4. On three (3) or more inches of concrete, racks may be stacked three (3) or four (4) units high.



CAUTION: Always inspect the surface of the area where racks are stored for any cracking or sinking and inspect the racks for tilting or leaning.



WARNING: Racks should not be stacked more than four (4) units high.

BUILD NOTE:

Do not overload the casters when stacking a rack on top of a rack that contains casters.

All material must be inspected prior to use! See inspection guidelines on page 87.



SCAFFOLD METAL BOARD STORAGE RACK

PART NUMBER	DESCRIPTION	WEIGHT (LBS.)	DIMENSIONS (INCHES) LENGTH X WIDTH X HEIGHT	MAX. CAPACITY (LBS.)
SBR	Steel Board Rack	160	59.75 x 47 x 36	5,000



Steel board racks are designed to hold InstantLock 2 metal boards and other irregularly-shaped components.

Steel board racks will hold 62 metal boards four (4) feet or longer and 124 metal boards 32 inches or shorter. When shipping, the metal board racks require two (2) pieces of banding to be placed around the base of the rack and the items being carried.

Steel board racks are designed so special casters can be placed on the bottom to allow the racks to be easily moved without a forklift. Always inspect rack feet for damage before installing casters or loading the rack.



STORAGE:

1. Steel board racks may be stacked for storage. The strength of the storage surface will determine how many racks can be stacked.
2. On grass, dirt or other unpacked surfaces, racks should be placed singly.
3. On prepared surfaces and asphalt, racks can be placed two (2) or three (3) high.
4. On three (3) or more inches of concrete, racks may be stacked three (3) or four (4) units high.



CAUTION: Always inspect the surface of the area where racks are stored for any cracking or sinking and inspect the racks for tilting or leaning.



WARNING: Racks should not be stacked more than four (4) units high.

All material must be inspected prior to use! See inspection guidelines on page 87.

BUILD NOTE:

Do not overload the casters when stacking a rack on top of a rack that contains casters.